

DS50VGPV-1000



- ↳ UL Type 1CA DC SPD
- Designed with High Energy MOV's
- Modular Design for Ease of Maintenance
- Integrated Status Indicator Window
- I_{max} : 40 kA /pole at 8/20μs
- I_n : 20 kA /pole at 8/20μs
- UL 1449 5th Edition Recognized



Electrical Characteristics		
Protection mode(s)		Common/Differential mode
POWER SPD TYPE		UL1449 TYPE 1CA
VOLTS	(V)	1000
AC/DC/DC PV/RF		DC PV & DC
PHASE	(PH)	-
AMPS	(A)	N/A
AMBIENT MIN	(C)	-35
AMBIENT MAX	(C)	+85
MODES		DC+G or DC-G
MCOV	(V)	1200/1200/1200
IN15 impulses 8/20μs	(kA)	20
SCCR	(kA)	50
Mechanical Characteristics		
Weight		0.294 kg
TECHNOLOGY		MOV+GSG
NETWORK CONFIGURATION		3 poles, 2W+G
CONNECTION METHOD		SPD-Screw Terminal (8-12AWG), Terminal blocks 6AWG
MOUNTING		DIN RAIL
MATERIAL		Thermoplastic UL94-V0
NEMA RATING (IP RATING)		NEMA 2 (IP20)
FAIL-SAFE BEHAVIOR		Disconnection via fuse-link
REAL-TIME DIAGNOSTICS		Visual indicator and remote contacts
DIMENSIONS		See diagram
Standards		
Certification		UL
UL STANDARD		UL1449 5th Edition
UL FILE NUMBER		E326289
Part number		
480351		