SPD Specific Disconnectors (SSD) for Type 1 AC SPD

SSD1-25S-40-230

- SPD Specific Disconnectors (SSD) for short circuit protection of Type 1 AC surge protectors
- Surge current withstand: 25 kA @ 10/350µs
- Wide range of short circuit current protected
- Reusable after switch triggered
- Low rated tripping current with time-current characteristics for overcurrent coordination with upstream OCPD and safety disconnect in case of SPD failure





электрические характеристики		
Макс. AC рабочее напряжение	Uc	400 Vac
Номинальный ток разряда	In	60 kA
Макс. ток разряда	Imax	120 kA
Импульсный ток на полюс	Iimp	25 kA
Эквивалентный номинальный переменный ток		315 A
Отключающая способность		100 000 A
Остаточное напряжение	Up	< 1.6 kV @ 6 kV (1.2/50 µs)
механические характеристики		
Формат		Одноблочный съёмный корпус
Монтаж		Симметричная DIN - рейка 35 мм (EN 60715)
Рабочая температура	Tu	-40/+85°C
Уровень защиты		IP20
Дистанционная сигнализация отключения		выход на перекидной контакт
Электропроводка для удаленной сигнализации		0.75 mm² max.
Макс. Напряжение / Ток для дистанционной сигнализации		240 V / 2 A (AC) , 24 V / 6 A (DC)
Размеры		см. схему
Вес		0.848 kg
Стандарты		
Соответствие стандартам		GB/T 18802.11 / IEC 61643-11 / NB/T 42150
Part number		
804114		